



Fire Alarm FPLP Solid Non-Shielded

300V, 75°C, Multi-Conductor, Unshielded, Solid Copper as FPLP. Minimum Operating Temperature 0°C, Maximum Operating Temperature 75°C




Image not to scale. See Table 1 for dimensions.

CONSTRUCTION:

1. **Conductor:** Solid bare copper per ASTM B3
2. **Insulation:** Low Smoke Polyvinyl Chloride (LS-PVC). Twisted multi-conductor
3. **Rip Cord:** Rip cord for ease of jacket removal
4. **Jacket:** Red Low Smoke Polyvinyl Chloride (LS-PVC)

APPLICATIONS AND FEATURES:

Fire protective signaling circuits. Also for smoke detectors, voice communications, audio control and initiating circuits. Article 760 of the NEC. For use in plenum spaces. Minimum Operating Temperature 0°C , Maximum Operating Temperature 75°C

SPECIFICATIONS:

- UL 1424 Cables for Power-Limited Fire-Alarm Circuits
- UL 1424 Listed FPLP
- NFPA 70, NFPA 101, and NFPA 502
- UL 13 Power-Limited Circuit Cables
- UL 444 Communications Cables (22 AWG - 16 AWG)
- RoHS-2 (European Directive 2011/65/EU)

SAMPLE PRINT LEGEND:

XX AWG X/C c{UL}US CMP/CL3P/FPLP 75°C -- CMP FT6 MADE IN USA ROHS-2 COMPLIANT -- {MM/DD/YY}
{HH:MM} {SEQUENTIAL FOOTAGE MARKS} SEQ FEET





Table 1 – Physical and Electrical Data

Stock Number	Cond. Size	Cond. Number	Cond. Strands	Diameter Over Cond.	Insul. Thickness	Jacket Thickness	Approx. OD	Copper Weight	Approx. Weight	DC Resistance @ 25°C	AC Resistance @ 75°C	Min Bending Radius
	AWG	No.	strands	inch	mil	mil	inch	lb / 1000ft	lb / 1000ft	Ω /1000ft	Ω /1000ft	inch
18 AWG												
20FAP-1802	18	2	Solid	0.040	10	15	0.144	9	15	6.669	8.035	0.5
20FAP-1804	18	4	Solid	0.040	10	15	0.168	19	28	6.669	8.035	0.6
20FAP-1806	18	6	Solid	0.040	10	15	0.184	30	41	6.669	8.035	1.1
16 AWG												
20FAP-1602	16	2	Solid	0.050	10	15	0.164	15	22	4.181	5.037	0.6
20FAP-1604	16	4	Solid	0.050	10	15	0.196	31	41	4.181	5.037	0.7
14 AWG												
20FAP-1402	14	2	Solid	0.064	10	15	0.196	25	33	2.631	3.170	0.7
20FAP-1404	14	4	Solid	0.064	10	15	0.226	50	61	2.631	3.170	0.9
12 AWG												
20FAP-1202	12	2	Solid	0.080	10	15	0.226	39	49	1.662	2.002	0.9

All dimensions are nominal and subject to normal manufacturing tolerances

