

SOOW, NON-UL PORTABLE CORD (8 AWG TO 2 AWG)

- Mining Cord
- 600 V
- 90°C
- 8 AWG - 2 AWG



APPLICATIONS:

Can be used in portable tools and equipment, temporary and portable power, motors and associated machinery.

CONSTRUCTION:

- 1 Conductor: Fully annealed stranded bare copper per ASTM B-174
- 2 Insulation: Premium-grade, color-coded 90°C EPDM
- 3 Jacket: CPE 90°C, black

STANDARDS & RATINGS:

- MSHA Approved
- RoHS Compliant

Part Number	No. of Conductors	Size (AWG)	Nominal Jacket Thickness	Nominal O.D.	Current Amps	Approx Net Weight (lbs/M)
07NUL-0802-01	2	8	0.050"	0.660"	40	278
07NUL-0803-01	3	8	0.050"	0.695"	40	343
07NUL-0804-01	4	8	0.050"	0.760"	35	442
07NUL-0805-01	5	8	0.050"	0.840"	28	542
07NUL-0602-01	2	6	0.050"	.7200"	55	355
07NUL-0603-01	3	6	0.050"	0.790"	55	482
07NUL-0604-01	4	6	0.050"	0.865"	45	599
07NUL-0605-01	5	6	0.050"	0.945"	36	750
07NUL-0402-01	2	4	0.050"	0.860"	70	515
07NUL-0403-01	3	4	0.050"	0.915"	70	683
07NUL-0404-01	4	4	0.050"	1.000"	60	851
07NUL-0405-01	5	4	0.050"	1.095"	48	1039
07NUL-0203-01	3	2	0.055"	1.085"	95	1003
07NUL-0204-01	4	2	0.055"	1.170"	80	1248
07NUL-0205-01	5	2	0.055"	1.390"	64	1648