

SOOW, UL/CSA PORTABLE CORD (8 AWG TO 2 AWG)

- Portable Cord
- 600 V
- 90 °C
- 18 AWG to 2 AWG



APPLICATIONS:

Can be used in portable tools and equipment, portable appliances, and small motors and associated machinery.

CONSTRUCTION:

- 1 Conductor: Fully Annealed Stranded Bare Copper Per ASTM B-174
- 2 Insulation: Premium-grade, color-coded 90°C EPDM
- 3 Jacket: CPE 90°C, black

STANDARDS & RATINGS:

- UL Flexible Cord - Subject 62
- CSA Flexible Cord
- MSHA Approved
- RoHS Compliant
- Temperature Rating: -40°C to 90°C

Part Number	No. of Conductors	Size (AWG)	Nominal O.D.	Current Amps	Approx. Weight
07B-1802-01	2	18	0.345"	10	65
07B-1803-01	3	18	0.365"	10	80
07B-1804-01	4	18	0.390"	7	94
07B-1602-01	2	16	0.370"	13	77
07B-1603-01	3	16	0.390"	13	94
07B-1604-01	4	16	0.420"	10	114
07B-1402-01	2	14	0.510"	18	154
07B-1403-01	3	14	0.535"	18	171
07B-1404-01	4	14	0.575"	15	209
07B-1202-01	2	12	0.570"	25	168
07B-1203-01	3	12	0.595"	25	223
07B-1204-01	4	12	0.650"	20	276
07B-1002-01	2	10	0.620"	30	230
07B-1003-01	3	10	0.660"	30	289
07B-1004-01	4	10	0.715"	25	351
07B-0803-01	3	8	0.840"	40	450
07B-0804-01	4	8	0.945"	35	580
07B-0805-01	5	8	1.030"	28	700
07B-0603-01	3	6	0.980"	55	637
07B-0604-01	4	6	1.080"	45	830

SOOW, UL/CSA PORTABLE CORD (8 AWG TO 2 AWG)

Part Number	No. of Conductors	Size (AWG)	Nominal O.D.	Current Amps	Approx. Weight
07B-0605-01	5	6	1.200"	36	1015
07B-0403-01	3	4	1.140"	70	926
07B-0404-01	4	4	1.260"	60	1145
07B-0405-01	5	4	1.365"	48	1419
07B-0203-01	3	2	1.330"	95	1367
07B-0204-01	4	2	1.460"	80	1699
07B-0205-01	5	2	1.580"	64	2066