

TRAY CABLE UL TYPE TC / TC-ER 600V 14 AWG XHHW-2 INSULATION - PVC JACKET

- Power Cable
- 600 V
- 90 °C
- 14 AWG



APPLICATIONS:

This Cable can be used in free air, raceways, and direct burial in wet or dry locations.

CONSTRUCTION:

- 1 Conductor: Stranded Bare Copper to ASTM-B3, Class B Stranding per ASTM-B8
Insulation: Flame-Retardant, Cross-Linked Polyethylene (XLPE) Color-coded per ICEA Method 1, Table E-2
- 2 Jacket: Flame-Retardant, Sunlight Resistant, Black Polyvinyl Chloride (PVC)

STANDARDS & RATINGS:

- UL 44 Type XHHW-2
- UL 1277 Type TC-ER for 3 or more conductors*
- UL 1581
- ICEA S-73-532
- UL 1581 VW-1
- UL 1277
- IEEE 383
- IEEE 1202
- ICEA T-29-520 (210,000 BTU/hr)
- CSA FT4
- EPA 40 CFR, Part 261
- OSHA Acceptable

Part Number	No. of Conductors	Size (AWG)	Nominal Jacket Thickness	Nominal O.D.	Approx. Weight (lbs/1M FT)
02A-1402-01	2	14	0.045"	0.365"	73
02A-1403-01	3	14	0.045"	0.390"	93
02A-1404-01	4	14	0.045"	0.425"	116
02A-1405-01	5	14	0.045"	0.465"	140
02A-1407-01	7	14	0.045"	0.590"	176
02A-1409-01	9	14	0.060"	0.620"	245
02A-1412-01	12	14	0.060"	0.680"	302
02A-1419-01	19	14	0.060"	0.800"	460
02A-1425-01	25	14	0.080"	0.985"	641
02A-1430-01	30	14	0.080"	1.050"	740
02A-1437-01	37	14	0.080"	1.130"	888