

TRAY CABLE UL TYPE TC / TC-ER 600V

POWER CABLE THHN/THWN OVERALL SHIELD -10 AWG

- Power/ Control Cable
- 600 V
- 90 °C
- 10 AWG
- Shielded



APPLICATIONS:

This Cable can be used in free air, raceways, and direct burial in wet or dry locations. Approved for direct burial, Class I, Div. 2 industrial hazardous locations per NEC. Permitted for Exposed Run use in accordance with NEC for 3 or more conductors.

CONSTRUCTION:

- 1 Conductor: Stranded bare copper to ASTM-B3, Class B stranding per ASTM-B8
- 2 Insulation: Color Coded Polyvinyl Chloride (PVC) with a Polyamide Nylon Covering
- 3 Jacket: Flame-retardant, Sunlight Resistant, Black Polyvinyl Chloride (PVC)

STANDARDS & RATINGS:

- UL 83 NEC Type THHN/THWN Conductors
- UL 1581
- FT4/IEEE 1202
- *UL 1277 Type TC-ER for 3 or More Conductors
- Rated for UV/Sunlight Resistant Applications
- Approved for Direct Burial

Part Number	No. of Conductors	Size (AWG)	Nominal Jacket Thickness	Nominal O.D.	Approx Weight (lbs/1M FT)
02A-1002S-01	2	10	0.045"	0.430"	119
02A-1003S-01	3	10	0.045"	0.460"	162
02A-1004S-01	4	10	0.045"	0.500"	205

